

## The Ennerdale Cantilever Walkway Technical Specification

### Vandal & Shatter Resistant



The Ennerdale's 5mm solid polycarbonate roof panels are resistant to all mechanical stresses both accidental and intentional, even when particularly heavy. It is therefore particularly suitable for use in areas where vandalism is a potential problem.

### Full Guarantee



The Ennerdale carries up to a full 10 year insurance backed guarantee for complete peace of mind.

### Maintenance FREE



The Ennerdale requires minimum maintenance. To clean the roof we recommend a solution of warm water and a non-abrasive cleaner.

### Strong Steel Structure



The strong cantilever frame is constructed from steel throughout. The posts have a width of 180mm upwards depending on the size of the structure.

## The Ennerdale Cantilever Walkway Technical Specification

### Weather resistance



During the manufacture of our polycarbonate panels a layer of UV absorber is co-extruded on both sides which forms a barrier giving high UV protection from the sun.

### Temperature Range



The polycarbonate's mechanical performance is known to remain stable in prolonged temperatures ranging from -50°C to +90°C.

### Choice of Colour



Glazing panels are available in a choice of clear and opal. The steel frame can be powder coated and or galvanised to BS EN ISO 1461:1999. If you choose a powder coated finish you can choose from any RAL colour.

© 2010 Able Canopies Limited All Rights Reserved. E&OE.  
MSS Ennerdale V1. Last updated 070910.