

The Ullswater Free Standing Canopy Technical Specification (Free Standing, Entrance Canopy, Walkway & Pyramid System)

The Ullswater provides an entirely new way to build a free standing canopy using a unique corner structure for ultimate strength and large self-supporting spans.

Resistant to breakage

Our polycarbonate panels are light in weight, up to 200 times stronger than glass and 10 times stronger than PVCu panels.



10 YEAR guarantee

Our canopies carry a full 10 year insurance backed guarantee for complete peace of mind.



Maintenance FREE

Our canopies require only periodic cleaning. To clean the roof we recommend a solution of warm water & a non-abrasive cleaner.



Choice of colour

Glazing panels are available in clear, opal & bronze. PVCu profiles are available in white & mahogany as standard. Other colours are available on request.



The Ullswater Free Standing Canopy Technical Specification

High pitch & low pitch

Fully variable roof pitch from lowest permitted pitch of 15 degrees with excellent water integrity.



Excellent insulation

Our 35mm "X" Structure polycarbonate panels offer the best insulation properties available.



Weather resistance

During the manufacture of our polycarbonate panels a layer of UV absorber is co-extruded onto the surface forming a barrier against UV radiation. All structural components are made from aluminium and PVCu for strength and total weather resistance.



Excellent fire performance

Our structured polycarbonate sheets have been tested to most European standards & to BS476 Part 7 & BS476 Part 6 with a Class 1 fire rating. They are classed as self-extinguishing & do not emit toxic gasses unlike PVCu panels.



© 2010 Able Canopies Limited All Rights Reserved. E&OE.
MSS Ullswater V3. Last updated 280610